

TEMPOMIX

Ref. 790BOX-790219

Time flow single control







DESCRIPTION

TEMPOMIX - Ref. 790BOX-790219



Recessed time flow shower kit:
 Waterproof recessing housing.
 Tamperproof polished stainless steel wall plate 160x220mm.
 10-30mm allowance for different wall finishes.
 TEMPOMIX 3/4" single control mixer.
 Ligature-resistant collar.
 Temperature control and operation on the push-button.
 Maximum temperature limiter (can be adjusted by the installer).
 Time flow ~30 seconds, soft-touch operation.
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof ROUND shower head with scale-resistant nozzle and automatic flow rate regulation.
 Concealed fixings, stopcocks M $\frac{1}{2}$ ".
 Integrated non-return valves and filters.
 Chrome-plated metal push-button.

ADVANTAGES

-  6 lpm
-  Wall recessed installation
-  Time flow system tested to over 500000 operations
-  Waterproof recessing housing

TECHNICAL FEATURES

TEMPOMIX - Ref. 790BOX-790219

Connector	1/2"
Technology	Time flow
Height	160mm
Width	220mm
Flow rate	6 lpm
Standards and certifications	 
Warranty	